

BEST AVAILABLE COPY

Amendments to the Specification:

On page 2, lines 2-9, please replace the paragraph with the following amended paragraph:

Line trimmers are used for a variety of applications in the yard. For example, they ~~function can be used~~ as mowing devices for cutting weeds and grass growing along fences or plants ~~beds~~ where a lawnmower cannot reach. For these applications, the head of the trimmer must be maintained horizontally so that the grass is cut evenly. Most of the trimmer wheeled accessories include two wheels that extend laterally from the trimmer's main pole. The wheels are located between the head of the trimmer ~~head~~ and the user thereby creating a fulcrum between the trimmer head and the handle. ~~The~~ During use, the fulcrum requires the user to move the handle up and down in an opposite ~~direction~~ directions relative to the trimmer head ~~during use~~.

On page 3, lines 4 and 5, please replace the paragraph with the following amended paragraph:

It is another object of the present invention to provide a trimmer wheeled accessory that ~~may supports the line trimmer in both head when cutting~~ horizontal and vertical ~~positions~~ paths.

On page 3, lines 6-8, please replace the paragraph with the following amended paragraph:

It is a further object of the present invention to provide a trimmer wheeled accessory that enables the user to easily adjust and maintain the ~~height of the trimmer head~~ at a constant height while walking.

On pages 3 and 4, lines 13-7, please replace the paragraph with the following

1 amended paragraph:

2 These and other objects of the present invention are met by a trimmer wheeled
3 accessory for a handheld, portable, gas or electric powered, line trimmer that selectively
4 attaches to the trimmer's main pole. The accessory includes an extension arm that attaches to
5 the trimmer's main pole and extends longitudinally and distally forward from the trimmer
6 head to support the trimmer head an even height on ~~on~~ above the ground during operation. The
7 extension arm includes an adjustable first clamp member used to attach the extension arm to
8 ~~approximately the trimmer's main pole.~~ The first clamp member allows the length of the
9 extension arm that extends beyond the trimmer head to be adjusted. The first clamp member
10 also allows the extension arm to axially rotate and laterally pivot around the main pole. The
11 This axial rotation feature allows the user to align the trimmer head for either vertical or
12 horizontal cutting. Attached to the distal end of the extension arm is a wheel assembly that
13 supports and allows the distal end of the extension pole to roll on the ground or grass. When
14 the accessory is attached to the main pole, ~~the~~ a fulcrum for the line trimmer is ~~located~~
15 created in front of the trimmer head. ~~This feature which provides greater control for the~~
16 user. In the preferred embodiment, the wheel assembly is able to rotate freely 360 degrees.
17 An optional clamp member may be provided between the wheel assembly and the distal end
18 of the extension arm that enables the wheel assembly to selectively rotate and lock in
19 different positions during use. This feature is especially useful when the user wants to align
20 the trimmer head in an offset position relative to the path of the wheel assembly.

21 On page 5 and 6, lines 23-6, please replace the paragraph with the following amended
22 paragraph:

23 In the preferred embodiment, the first clamp member 20 includes a lower clamp

1 member 23 with an adjustable strap 22 that attaches to the main pole 92, ~~via the adjustable U-~~
2 ~~shaped strap 22.~~ Attached to the lower clamp member 23 is a rotating upper clamp member
3 21. ~~Disposed~~ As shown in Fig. 10, disposed between the lower clamp member 23 and upper
4 clamp member 21 is a handle 25 mounted on a and center post 26 that interconnects with the
5 strap 22 to tighten or loosen the strap 22 around the main pole 92. A more detailed
6 description of the first clamp member 20 is discussed below.

7 On page 6, lines 9-11, please replace the paragraph with the following amended
8 paragraph:

9 The wheel assembly 50, shown more clearly in Figs. 1, 3, 5 - 7, includes an upper
10 adapter 52 that securely attaches to the distal end 11 of the extension arm 10. Rotatingly
11 attached to the upper adapter 52 is a lower adapter 56.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.